

# UV-PROTECTED RAINSCREEN INSTALLATION INSTRUCTIONS

invisiwrap® uv

hydroflash® uv+

batten uv

## 20 YEAR PRODUCT WARRANTY REQUIREMENTS

### APPROVED COMPATIBLE PRODUCTS

#### SELF-ADHERED FLASHING

Benjamin Obdyke® HydroFlash® UV+  
SIGA™ Wigluv Black

#### BATTENS/FURRING STRIPS

Benjamin Obdyke® Batten UV  
Wood Furring Strips

#### CAULKS AND SEALANTS

HydroFlash® LA  
OSI® QUAD® MAX Sealant  
Loctite® Premium® Construction Adhesive  
Loctite® PL Premium® S40 Polyurethane  
GeoCel® 2300 Construction Tripolymer  
GeoCel® Pro Flex®  
Fortifiber® Moistop® Sealant  
Bostik® 915™ Polyurethane Sealant  
Bostik® 915FS™ Polyurethane Sealant  
Dow Corning® 732 Multi-Purpose Sealant  
NPC® Solar Seal #900  
Titebond® Heavy Duty Construction Adhesive  
Titebond® WeatherMaster™  
Titebond® WeatherMaster™ ULTIMATE MP  
Tremco® Vulkem® 116  
DAP® Flexible Clear Sealant

#### VIRTUAL JOBSITE VISIT

Project specific installation training and window mockups are recommended to verify proper details and reduce the learning curve for installers and design professionals.

To ensure you're achieving the maximum warranty, please contact us at [techsupport@obdyke.com](mailto:techsupport@obdyke.com), or fill out the request form on our website,

**OR SCAN THE QR CODE HERE.**

